



Panels

Bekazur Classic and Bekazur 2D are panel systems for the protection of swimming pools, its execution makes it conform to the norm, rigid, multifunctional and elegant.

Bekazur[®] Classic and Bekazur[®] 2D

BENEFITS

Conformity

The systems conform to the norm NF 90-306 designed to restrict the access to swimming pools for children younger than five years old. The norm defines the technical characteristics of the system and resistance to corrosion of all metallic parts.

Specific fixing system of the gate

The gate is secured by a fixing system that can only be opened by 2 simultaneous and independent actions.

Multifunctional

The installation of Bekazur is very simple. It can be installed on base plate or in concrete. Installation on sloping ground is also possible.

Elegance

The rounded profile makes the fence simple and aesthetic. Whatever version you choose, tubular or double bar with decorative top.


Applications

Swimming pools.

Bekazur[®] Classic



Bekazur[®] 2D



Panels

Bekazur Classic is a welded tubular panel.

- Vertical round tubes: \varnothing 16 x 1,5 mm
- Distance between 2 vertical tubes: 94 mm
- Dimension horizontal rounded profile: 40 x 20 mm
- Adaptable support point in the middle of the panel of 200 cm.

Bekazur 2D is a panel system with rigid galvanised wires and welded afterwards.

The heavy diameter of the wires makes the panel highly resistant.

- Horizontal wires: 7,65 / 8,00 mm
- Vertical wires: 7,65 / 8,00 mm
- Distance between 2 vertical wires: 65 mm
- Minimum distance between 2 horizontal supporting points: 1100 mm

Posts



The panels can be installed with:

- Round post diam. 48 X 1,50 mm with cap
- Galvanised and plastic coated white ral 9010.

Special brackets
Bekazur 2D or Bekazur Classic in polyamide are used for the fixation of the panel to the post.



Accessories

For installation on a concrete or tiled floor:
aluminium base plate, white plastic coated,
diameter 48 mm + stainless screw m8 x 15 mm.



Coating

Bekazur Classic:

Panels: hot dipped galvanised after welding + polyester coated.
Posts: galvanised two sides (min. layer 275 g/m², 2 sides combined). Adhesion coating + polyester.
Thickness: min. 100 Microns

Bekazur 2D: welded out of galvanised wires + polyester coated

ASSORTMENT BEKAZUR PANELS

Fence height mm	Dimensions panels width x height mm
Bekazur Classic	
1100	1000 x 1100
1100	2000 x 1100
1300*	2000 x 1300
Bekazur 2D	
1196	983 x 1196
1196	2023 x 1196
1396*	2023 x 1396

* For installation on slope ground

Colour

White RAL 9010

Gates



Available in the two models (tubular or with wires).

Hot dipped galvanised + polyester coating.

- Adjustable stainless steel hinges
- Round posts d. 60 X 2.00 mm.
- Security locking system 'double action' + cylinder supplied with 3 keys.
- Options: automatic lock system made of 2 hinges with integrated springs, which replace the ones supplied with the gates.



Gates available in 2 versions:

Post to be put in concrete or posts welded on a base plate for installation on concrete soil.

Installation

It is important to assure oneself when installing the posts in massive concrete that all redundant water is evacuated in a proper way.

ASSORTMENT BEKAZUR POSTS

Bekazur fence height mm	Bekazur 2D fence height mm	Post length mm	Installation type
1100	1196	1250	base plate
1100	1196	1600	concrete
1300	1396	1450	base plate*
1300	1396	1800	concrete*

* For installation on slope ground

ASSORTMENT BEKAZUR GATES

Fence height mm	Post length mm	Gate width mm	Post diameter mm
Bekazur Classic			
1100	1240	1150	60*
1100	1700	1150	60**
Bekazur 2D			
1196	1349	1275	60*
1196	1800	1275	60**

* With 2 posts diam. 60 x 2,00 mm with welded base plates for installation on hard floor (4 collets diam. 60 mm incl.)

** With 2 posts diam. 60 x 2,00 mm for installation in concrete (4 collets dia. 60 mm incl.)

